

# BL-E

## Hollowed Load Cell



### Large capacity type ideal for field measurement



- Rated capacity: 1, 2 MN

These center hole load cells measure ground anchor and PC anchor loads, and also measure loads applied during tunnel arch support work.


#### Models

Model	Rated Capacity	φA	φB	φC	φD	φE	(G)	H	Weight (Approx.)
BL-100TE	1 MN	85 <sup>+3</sup> <sub>0</sub>	98 <sup>+1.5</sup>	128 <sup>+1.5</sup>	140 <sup>+2</sup>	113 <sup>+0.3</sup>	71	110 <sup>+0.5</sup>	6.6 kg
BL-200TE	2 MN	133 <sup>+3</sup> <sub>0</sub>	150 <sup>+1.5</sup>	190 <sup>+1.5</sup>	210 <sup>+2</sup>	170 <sup>+0.5</sup>	106	120 <sup>+0.5</sup>	14.1 kg

#### Dimensions



Bared at the tip (standard)



#### Specifications

##### Performance

Rated Capacity	See table below.
Nonlinearity	BL-100TE: Within ±0.5% RO BL-200TE: Within ±1.5% RO
Hysteresis	Within ±1% RO
Rated Output	1 mV/V or more

##### Environmental Characteristics

Safe Temperature	-20 to 70°C
Compensated Temperature	-10 to 60°C
Temperature Effect on Zero	Within ±0.1% RO/°C
Temperature Effect on Output	Within ±0.1%/°C

##### Electrical Characteristics

Safe Excitation	10 V AC or DC
Recommended Excitation	1 to 10 V AC or DC
Input Resistance	350 Ω ±2%
Output Resistance	350 Ω ±2%
Cable	4-conductor (0.5 mm <sup>2</sup> ) chloroprene shielded cable, 9.6 mm diameter by 1 m long, bared at the tip (Shield wire is not connected to the case.)

##### Mechanical Properties


Safe Overloads	120%
Weight	See table below.

#### Optional Accessories

Saddle for BL-type load cells

Dimensions (D) and (t) are available in the following range depending on rated capacity.  
D = 100 x 100 mm to 400 x 400 mm  
t = 20 to 50 mm

\*Inform us the dimensions of the part of equipment which contacts with the saddle.  
\*A round saddle is also available for option.



1  
-246

Sensor



Strain Gage

Load Cell

Pressure Sensor

Acceleration Sensor

Torque Sensor

Displacement Sensor

Component Force Sensor

Automotive Sensor

Civil Engineering Sensor