

# BX24 / BX24D Weighing Indicator

Power & performance for weighing applications



## Main Features

- Stainless steel, IP67 protected for wet, hygienic and harsh areas
- Color changing display, SmartAPP 16 digit alphanumeric info line,
- ID1, ID2, PT, item limit values, APW memories; each 500 items record
- Automatic memory linkage to IDs



## High Technology & Performance

- High resolution scales up to 999 999 display resolution
- Up to 800 conversions per second
- Application based SmartAPP
- Changing color for prompting
- High capacity tank scales supported by eCAL - electronic calibration



## Typical Applications

- Weighing and data collection
- Customized labelling with barcode
- Counting by sample & APW memory
- Livestock and dynamic weighing with strong filtering algorithm
- Checkweighing, classifying & filling
- Specific tare entry requirement



## Interfaces & Communication

- 2 x RS232C, RS485, Ethernet TCP/IP and USB are standard,
- Printing via key, digital input, and serial port
- Continuous data output
- BSI command set for master slave communication



BX24 & BX24D are accurate, multifunctional weighing terminals which can be used in wet, hygienic and harsh industrial areas. Terminals have configurable operating modes for common weighing applications such as weighing, labelling, piece counting, checkweighing, classifying, dynamic weighing and filling. Depending on the application, 3 programmable keys can be set to related functions for quick and easy operation.

Instruments have 6 memories; ID1 & ID2, preset tare, APW and item limit values; each have 500 records capacity. IDs can be linked to other memory records for fast, easy and reliable operation; when an ID is selected, depending on the operation mode item limit values, specific tare or APW values comes automatically.

BX24 & BX24D offer direct connection to remote display, PC and PLCs via various data protocols such as demand, continuous form and BSI command set.

**BAYKON**  
Industrial Weighing Systems

# Typical Applications

## 1. Labeling & Data Collecting

BX24 & BX24D can print different type of standard tickets including totalizing and customized ticket with barcode.

## 2. Piece Counting

Counting can be done by sampling or average piece weight taken from APW manual. 500 item memory capacity for APW.

## 3. Checkweighing

The weight or the quantity of the items in the package is checked. 500 item memory for limits set.

## 4. Classifying

Products can be classified according to the weight or the quantity of item in the package. 500 item memory for limits set.

## 5. Gravimetric Filling

Automatic / manual filling can be executed in gross mode or in net mode. 500 item memory for limits set.

## 6. Dynamic and Livestock Weighing

Weighing of dynamic items such as livestock is available by BX24 & BX24D. This feature is also usable for weighing at static scales under vibration of industrial environments.



# Technical Specifications

Model	BX24	BX24DI	BX24DL
Accuracy class & EU type approval	OIML class III, single range, multi range or multi interval		
Display	Wide angle LCD display with multicolor backlight, 6 digits 22 mm in height weight display and 16 digits 8 mm in height alphanumeric information display		
Display resolution	Up to 999 999 division	Please refer to the following digital load cells	
A/D conversion	24 bit Delta-Sigma ADC with up to 800 conversion rate	All Baykon digital load cells; BR016D, BR030 / 32SD, BS063SD, BR200SD, etc. & Flintec RC3D.	
Minimum input sensitivity	0.4 µV/d (legal metrology), 0.05 µV/d (industrial)		
Analogue input range	-5 mV to +19 mV		
Internal resolution	Up to 16 000 000 counts		
Calibration	Standard calibration tests with test weights eCAL: electronic calibration without test weight, span adjustment of non-empty tanks		
Digital filter	5 step adjustable digital adaptive filter and 5 programmable digital dynamic filter		
Functions	2 x ID data, ticket number, date & time, total indication, ID1 & ID2 header definition as Customer, Material, Quality, Color, etc.		
Standard applications	Labelling, piece counting, totalization of the sequential weighing, totalization of the additive items, livestock weighing, checkweighing, classifying, filling		
Memory	ID1 and ID2 memories, specific tare memory, item limit values memory for basic weighing, filling, classifying and check weighing, average weight of items memory for piece counting. Each memory has 500 record capacity		
SD card	SD card slot for different applications		
Programmable keys	3 pieces programmable function keys		
Digital inputs	Opto isolated 4 inputs programmable for zeroing, taring, print, PLC remote input, etc. Inputs are set automatically to certain functions at checkweighing, classifying, filling etc.		
Digital outputs	Relay contact outputs are programmable as cut off, PLC remote outputs.		
Data output	Galvanically isolated 2 pcs RS232C, RS485 serial ports , Ethernet TCP/IP and micro USB		
Number of load cells	Up to 8 load cells 350 Ω or up to 24 load cells 1200 Ω (min. 43 Ω)	Up to 4 digital load cells	Up to 24 digital load cells with lightning protected by the LPK24D.
Load cell connection	Connection with 4 or 6 wires. Cable length maximum 1000 m/mm <sup>2</sup>	RS485, Home Cable max. 300m	
Alibi memory	99 999 weighing records		
Operation temperature	-15°C ~ +55°C max. ( Operational ), -10°C ~ +40°C ( Legal metrology )		
Humidity	Max. 90 % non condensing relative humidity. Legal metrology max. 80 %		
Housing and protection class	Desk top and wall type stainless steel, IP67 protected		
Power supply	100 - 240 VAC, 50/60 Hz or 12 - 28 VDC		
<b>Options</b>			
Scale options	Digital 4 inputs / 5 outputs, Analogue output, Alibi memory		
Accessories	Column mount kit, Wall mount kit, 2D Wall mount kit		