OFF CENTER LOAD CELL TYPE SUP15 - 02

Applications:

Off centre load cell Type SUP15-02 can be used in small capacity weighing systems.

Some applications are:

- Small weighing platforms
- Electronic scales

Main features:

- Universal use
- Low cost
- Aluminium construction
- Independent from centre of load application
- Platform size 200X200 mm
- Atex certification

Nominal load:

Kg 0.5-1-3-5-10-15

CELMI s.r.l.
Largo Brugnatelli 13/16
20090 Buccinasco (MI)
Italy

Tel: +39 0245712209
Fax: +39 0245705836
info@celmi.com
celmi.com

Specification in according to VDI/VDE 2637

Metrological Characteristics	Par.	Un.	
Nominal Load	Ln	Kg	0,5÷15
Initial Load	Lp	%Ln	20
Maximum Load	Ll	%Ln	150
Linearity	Flin	±%Ln	0,05
Hysteresis	Fu	±%Ln	0,05
Repeatibility	Fv	±%Ln	0,05
Creep (in 30')	Fcr	±%Ln	0,05
Nominal Temperature Range	Btn	°C	-10+40
Zero Temperature Drift (10÷60°C, over 10°C)	TK0	±%Cn	0,005
Output Temperature Drift (10÷60°C, over 10°C)	TKC	±%Cn	0,005
Thermal Gradient		K/h	<5

Electrical Data			
Nominal Output	Cn	mV/V	2
Nominal Output Tolerance	Dc	±%Cn	5
Nominal Supply Voltage	Bsu	V	0,5÷12
Maximum Supply Voltage	Usmax	V	15
Input Resistance	Re	Ω	410±15%
Output Resistance	Ra	Ω	350±3%
Insulation Resistance @20V	Ris	MΩ	>2000
Zero balance	Do	±%Cn	±2

Mechanical Data			
Breaking Load	Ld	%Ln	200
Maximum Side Load	Llq	%Ln	100
Deflection	hn	mm	<1
Cable Lenght		mm	2000
Weight		Kg	0,2

Environmental Conditions			
Working Temperature Range	Btn	°C	-20+60
Storage Temperature Range	Bts	°C	-20+60
Housing Protection			IP -65

Subject to change without notice

CELMI s.r.l.
Largo Brugnatelli 13/16
20090 Buccinasco (MI)
Italy

Tel: +39 0245712209
Fax: +39 0245705836
info@celmi.com
celmi.com

Dimensions: (in mm; 1mm = 0.03937 inches)