



OFF CENTER LOAD CELL TYPE SUP22



Applications:

Off centre load cell type SUP22 can be used in small capacity weighing systems.

Some applications are:

- Small weighing platforms

Main features:

- Universal use
- Low cost
- Aluminium construction
- Independent from centre of load application
- Platform size 250X300 mm
- Atex certification

Nominal load:

Kg 25-50-80



**OFF CENTER
LOAD CELL
TYPE SUP22**

Specifiche in accordo con VDI/VDE 2637

Metrological Characteristics	Par.	Un.	
Nominal Load	Ln	Kg	25÷80
Initial Load	Lp	%Ln	20
Maximum Load	Ll	%Ln	150
Linearity	Flin	±%Ln	0,02
Hysteresis	Fu	±%Ln	0,02
Repeatability	Fv	±%Ln	0,02
Creep (in 30')	Fcr	±%Ln	0,03
Nominal Temperature Range	Btn	°C	-10+40
Zero Temperature Drift (10÷60°C, over 10°C)	TKo	±%Cn	0,02
Output Temperature Drift (10÷60°C, over 10°C)	TKC	±%Cn	0,03
Thermal Gradient		K/h	<5

Electrical Data			
Nominal Output	Cn	mV/V	2
Nominal Output Tolerance	Dc	±%Cn	10
Nominal Supply Voltage	Bsu	V	1÷10
Maximum Supply Voltage	Usmax	V	15
Input Resistance	Re	Ω	1130±15%
Output Resistance	Ra	Ω	1000±10%
Insulation Resistance @20V	Ris	MΩ	>2000
Zero balance	Do	±%Cn	±2

Mechanical Data			
Breaking Load	Ld	%Ln	200
Maximum Side Load	Llq	%Ln	100
Deflection	hn	mm	<1
Cable Length		mm	1500
Weight		Kg	0,2

Environmental Conditions			
Working Temperature Range	Btn	°C	-20+60
Storage Temperature Range	Bts	°C	-20+60
Housing Protection			IP -65

Subject to change without notice

Dimensions:

(in mm; 1mm = 0.03937 inches)

