

Specifications

Eaton MTL7710P+

Eaton Crouse-Hinds series MTL7700 Zener barrier, 10 Vdc, 300mA, Polycarbonate, DIN rail mount, + polarity

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
CATALOG NUMBER	MTL7710P+
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	12.6 mm
PRODUCT WEIGHT	140 g
PRODUCT TYPE	Zener barrier



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION Hazardous/Classified Locations

STANDARDS TYPE NEC/CEC
IECEX/ATEX
IEC

NEC HAZARDOUS RATING Class I, Zone 2
Class I, Division 2

IECEX/ATEX HAZARDOUS RATING Zone 0
Zone 2

INGRESS PROTECTION (IP) RATINGS IP20

Product specifications

RATED SUPPLY VOLTAGE DC 10 Vdc

TYPE OF POWER SUPPLY DC

SWITCHING CURRENT 300mA

MATERIAL Polycarbonate

MOUNTING METHOD DIN rail

MINIMUM OPERATING TEMPERATURE -20 °C

MAXIMUM OPERATING TEMPERATURE 60 °C

Resources

INSTALLATION INSTRUCTIONS [MTL7700 ATEX Safety Instructions](#)

TECHNICAL SERVICE BULLETINS [MTL7700 Range datasheet](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2026 Eaton. All Rights Reserved.