


# Specifications



## Eaton MTL7767+

Eaton Crouse-Hinds series MTL7700 Zener barrier, Dual MTL715, 15 Vdc, 150mA, Polycarbonate, DIN rail mount, + polarity

### General specifications

|                             |   |
|-----------------------------|---|
| <b>PRODUCT NAME</b>         | Eaton Crouse-Hinds series MTL7700 Zener barrier |
| <b>PRODUCT NAME</b>         | Eaton Crouse-Hinds series MTL7700 Zener barrier |
| <b>CATALOG NUMBER</b>       | MTL7767+  |
| <b>EAN</b>                  | 3066227675718                                   |
| <b>PRODUCT LENGTH/DEPTH</b> | 105 mm  |
| <b>PRODUCT HEIGHT</b>       | 90 mm   |
| <b>PRODUCT WIDTH</b>        | 12.6 mm   |
| <b>PRODUCT WEIGHT</b>       | 140 g   |
| <b>PRODUCT TYPE</b>         | Zener barrier                                   |



Powering Business Worldwide

## Certifications and compliances

|  |  |
|--|--|
| <b>AREA CLASSIFICATION</b>             | Hazardous/Classified Locations         |
| <b>STANDARDS TYPE</b>                  | IEC<br>IECEX/ATEX<br>NEC/CEC           |
| <b>NEC HAZARDOUS RATING</b>            | Class I, Zone 2<br>Class I, Division 2 |
| <b>IECEX/ATEX HAZARDOUS RATING</b>     | Zone 2<br>Zone 0                       |
| <b>INGRESS PROTECTION (IP) RATINGS</b> | IP20                                   |

## Resources

|                             |  |
|-----------------------------|--|
| INSTALLATION INSTRUCTIONS   | <a href="#">MTL7700 ATEX Safety Instructions</a> |
| TECHNICAL SERVICE BULLETINS | <a href="#">MTL7700 Range datasheet</a>          |

## Product specifications

|                                      |               |
|--------------------------------------|---------------|
| <b>TYPICAL APPLICATION</b>           | Dual MTL715   |
| <b>RATED SUPPLY VOLTAGE DC</b>       | 15 Vdc        |
| <b>TYPE OF POWER SUPPLY</b>          | DC            |
| <b>SWITCHING CURRENT</b>             | 150mA         |
| <b>MATERIAL</b>                      | Polycarbonate |
| <b>MOUNTING METHOD</b>               | DIN rail      |
| <b>MINIMUM OPERATING TEMPERATURE</b> | -20 °C        |
| <b>MAXIMUM OPERATING TEMPERATURE</b> | 60 °C         |

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

