


Specifications



Eaton MTL7788R+

Eaton Crouse-Hinds series MTL7700 Zener barrier, For 1-5V systems, 28 Vdc, 93mA, Polycarbonate, DIN rail mount, + polarity

General specifications

PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
PRODUCT NAME	Eaton Crouse-Hinds series MTL7700 Zener barrier
CATALOG NUMBER	MTL7788R+
EAN	3066227675711
PRODUCT LENGTH/DEPTH	105 mm
PRODUCT HEIGHT	90 mm
PRODUCT WIDTH	12.6 mm
PRODUCT WEIGHT	140 g
PRODUCT TYPE	Zener barrier



Powering Business Worldwide

Certifications and compliances

AREA CLASSIFICATION	Hazardous/Classified Locations
STANDARDS TYPE	IECEX/ATEX NEC/CEC IEC
NEC HAZARDOUS RATING	Class I, Zone 2 Class I, Division 2
IECEX/ATEX HAZARDOUS RATING	Zone 0 Zone 2
INGRESS PROTECTION (IP) RATINGS	IP20

Resources

INSTALLATION INSTRUCTIONS	MTL7700 ATEX Safety Instructions
TECHNICAL SERVICE BULLETINS	MTL7700 Range datasheet

Product specifications

TYPICAL APPLICATION	1-5V systems
RATED SUPPLY VOLTAGE DC	28 Vdc
TYPE OF POWER SUPPLY	DC
SWITCHING CURRENT	93mA
MATERIAL	Polycarbonate
MOUNTING METHOD	DIN rail
MINIMUM OPERATING TEMPERATURE	-20 °C
MAXIMUM OPERATING TEMPERATURE	60 °C

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

